B700 Series Specifications





The B721 and B731 A4 mono printers bring fast, reliable printing to the busy workgroup by combining advanced security, management and performance with robust and durable LED technology.

They offer print speeds of up to 52ppm for enhanced office efficiency and improve workgroup productivity by deploying a fast processor with ample memory to tackle complex and high volume print jobs.

Both models have first page out times are as little as 5 seconds and offer a flexible paper source with multiple input trays and a maximum input capacity of 3,160 sheets. The versatile engine has a monthly duty cycle of 200K prints and can confidently handle a variety of applications in any working environment.

The B731dnw with its high yield print cartridge reduces user intervention rates and for added versatility offers wireless connection that allows you to place your printer wherever is most convenient.

Improving business productivity

- Up to 52ppm print speed and time to first print, less than 5 seconds
- Standard duplex, for paper saving
- Paper capacity of up to 3,160 sheets
- Up to 200K monthly duty cycle
- Three year on-site warranty on registration of your product within 30 days

Fast Processing

- 800MHz processor and 256MB RAM memory
- Optional 160GB Hard Disk Drive
- Wireless connectivity as standard (B731dnw)
- 10/100/1000 baseT Ethernet

Highest level document and data security

Including security and encryption to the highest industry standards, the B700 Series provides sophisticated user authentication that prevents unauthorised access to your corporate data.

- Secure Print job encryption
- SNMPv3 and IPSec secure networking
- 802.1X network protocol and IP/MAC filtering access control
- Secure Print with numeric keypad for easy PIN code entry

Excellent print quality

- 1200 x 1200dpi print resolution ensures pinsharp output every time
- Flexible media handling up to 253gsm and 1.3m banners


Reducing your impact on the environment

OKI technology and in-built eco features ensure that the B700 Series is both efficient and environmentally friendly.

- Double sided printing for reduced paper usage
- High yield toner cartridge up to 36K reducing capital and consumable costs
- Toner save function
- 1.5W or less in Deep Sleep mode (B721dn)
- Energy Star certified

Mobile printing

Print effortlessly from your smarphone or tablet. This printer is compatible with AirPrint by Apple Inc, Cortado Workplace and ePrint by Microtech Corp, enabling you to print where ever you are, without having to connect directly to a printing device



Variants available:

B721dn duplex, networked B731dnw duplex, networked, wireless



B721dn and B731dnw - Mono Printers

A / Duint au 1	P721dn, /7nnm, P721dnus F2nnm
A4 Print speed	11 1
Time to first print Warm up time	Less than 5 seconds 25 seconds or less from power on (B721dn), 60 seconds from power on (B731dnw), 19 seconds or less from power save (B721dn, B731dnw)
Processor speed	
PRINT QUALITY	
Resolution	1200 x 1200dpi, 600 x 600dpi
Typefaces	
Printer fonts	Scalable: 87 PCL fonts & 136 PostScript fonts, Line Printer, OCR-A/B, USPS ZIP Barcode
Dot matrix fonts	Epson FX, IBM-PPR
Barcode	10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, 2 types of two dimensions: PDF417, QR code
INTERFACE AND SOFTWARE	
Connectivity	B721dn: 10/100/1000 baseT, High Speed USB x 2 (1x type A & 1x type B) B731dnw: 10/100/1000 baseT, Wireless LAN 802.11b/g/n, High Speed USB x 2 (1x type A & 1x type B)
Printer languages	PCL5e, PCXL, Postscript 3 Emulation, XPS, Epson FX, IBM PPR
Network & protocols	B721dn, B731dnw: All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPV4&v6, Net Bios over TCP, SMTP, HTTP, HTTPS, SNMPP1&v3, DHCP, DNS, IPP, IPPS, BOOTP, DDNS, WINS, UPnP, SNTP, IGMP, IGMPV2, ICMP, IMCPV6, LPR, Port9100, FTP, Telnet, Bonjour, LLTD, Web Service on Devices. AirPrint. B731dnw: Wireless LAN Protocol (IEEE802.11b, IEEE802.11g, IEEE802.11n, Infrastructure Mode, WEP, WPA(TKIP), WPA2(AES), WPS-PBC, WPS-PIN, Open system authentication, Shared key authentication, IEEE802.1x authentication)
OS Compatibility ¹	Windows 8 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Vista SP1 & SP2 (32-bit & 64-bit) / XP SP2 or later / Server 2008 SP1 or later (32-bit & 64-bit) / Server 2003 SP2(32-bit & 64-bit) / Server 2008 X 10.4/10.5/10.6/10 7/10.8; PPDs for Linux/Unix
Utility suite¹	Print Job Accounting ² , Print Job Accounting Client ² , PrintSuperVision.NET ² , Template Manager ² , Universal PCL Print Driver ² , Configuration Tool ² , OKI LPR Utility ² , PDF Direct Print ²
SECURITY	
Device Security	IP Filtering, MAC Filtering, IPSec, Secure Print, Secure Print job encryption, SMTP server authentication, SNMPv3, SSL/TLS Encryption, Port Change, Storage Device Encryption, Secure Erase, Disable Host USB feature, Protocol ON/OFF

Р٨	DE	o ⊦	lar	וחו	ING

Standard Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Optional Paper capacity	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; Tray 4: 530 sheets of 80gsm; Large Capacity Feeder: 2,000 sheets of 80gsm
Paper Input capacity	Standard: Up to 630 sheets of 80gsm; Maximum: Up to 3,160 sheets of 80gsm
Paper sizes	Tray 1: A4, A5, B5; Tray 2/3/4: A4, A5, B5; Large Capacity Feeder: A4; Multi-purpose tray: A4, B5, A5, A6. Envelopes (Com-9, Com10, DL, C5), Supports custom size: Width 76-216mm Length 127-1321mm; Duplex : A4, B5. Supports custom size: Width 148-216mm Length: 210-356mm
Paper weight	Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 220gsm; Large Capacity Feeder: 64 to 220gsm; Multi-purpose tray: 64 to 253gsm; Duplex: 64 to 220gsm
Duplex	Standard
Paper output	Face up: 100 sheets of 80gsm, Face down: 500 sheets of 80gsm

GENERAL FEATURES

Memory	Standard RAM: 256MB; Maximum RAM: 768MB
Wellioty	Optional HDD: 160GB
Environment	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
	Storage temperature/ humidity: -10°C to 43°C / 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/- 2%
Power consumption	Typical: 800W (B721dn), 850W (B731dnw); Max: 1400W; Idle: 95W; Power Save: 19W (B721dn), 22W (B731dnw); Deep Sleep: 1.5W or less (B721dn), 3.9W or less (B731dnw)
Noise level	Operating: 55dB(A) or less (B721dn), 57dB(A) or less (B731dnw); Quiet Mode: 53dB(A); Standby: 30dB(A); Power save: Background level
Dimensions (HxWxD)	410 x 435 x 498mm
Weight ³	27kg approx
Duty cycle	Average: 20,000 pages/month (B721); 30,000 pages/month (B731dnw); Maximum: 200,000 pages/month
Warranty	3 years extended warranty upon registration within 30 days of purchase
Product order number	B721dn: 01334001; B731dnw: 01334101

ACCESSORIES (ORDER NUMBERS)

Paper Feeders	2nd/3rd/4th paper tray: 45478902; Large Capacity Feeder: 45530102
Castor base	45478702
Hard Disk Drive	160GB: 44622305
Memory	512MB: 01182908

CONSUMABLES (ORDER NUMBERS)

CONSONIABLES (OKDER NOMBE	CONSUMABLES (ORDER NUMBERS)		
Print cartridge* (18,000 pages)	45488802 (B721/B731)		
Print cartridge* (36,000 pages)	45439002 (B731)		
Maintenance Kit (200,000 pages)	45435104		

^{*}Toner: Number of A4 pages @ ISO/IEC 19752 coverage. Printer shipped with toner for 10,000 pages @ ISO/IEC 19752.

¹Check local OKI website for latest driver releases and OS compatibility; ²Windows only; ³Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.



3 Year On-Site Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit: www.oki.co.uk/warranty. Without registration, the standard pan-European 1 year warranty applies.











OKI SYSTEMS (UK) LTD

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 1784 274300 F +44(0) 1784 274301



